

BAUTECH SEC RÁPIDO®

THE PRODUCT

Super Flexible waterproofing with high performance and fast drying. It can be used in damp substrates and has a 10 year warranty, if applied as recommended.

FIELDS OF APPLICATION

- Slabs, walls and cement reservoirs in residential, commercial and industrial environments.

KEY FEATURES

- Quick dry
- It can be applied to moist substrate
- High resistance to sun and rain
- Resists positive and negative pressures
- Product water based and free of VOC
- Forms a flexible and waterproof membrane



PACKAGING KIT A+B	26,46 lb (12kg)
COVERAGE (conventional applications)	86,11 ft² / kit (8m²/kit)
COLOR	Beige
COATS REQUIRED	3 (three coats)
INTERVAL BETWEEN COATS	1 hour
OPEN FOR TRÁFIC	12 hours
WORK TIME	30 minutes
FACTOR WATER	4,23 qt/package
VALIDADE	24 months from date of manufacture

SUBSTRATE PREPARATION

- The surface to be sealed must be cement based, properly clean free of dust grease or oil.
- Do not apply the product on bituminous surfaces, as asphalt and tar
- To clean the substrate, is recommended the use of mild detergent and water in abundance.
- For use in new slabs is required to wait a minimum of 15 days for the concrete curing
- The surface must be smooth, stable, firm and without detached particles.
- If there are drains, is important to realize a variation level of at least 1% gap.
- Fissures, cracks must be pretreated with a sealants or BAUTECH CRACK TAPE®
- All the edges and sharp corners must be slightly rounded.

PRODUCT PREPARATION

- In a clean container add 4,23 qt (4 liters) liters of water.
- Add the 26,46 lb (12kg) of BAUTECH SEC RÁPIDO gradually, under constant stirring with mechanical mixer aid , for 4-5 minutes or until obtain a smooth paste.

APPLICATION

- *Moisten the base few minutes before the application.*
- *Apply BAUTECH SEC RÁPIDO with the aid of a brush in 3 coatings, with 1 hours intervals.*
- *The minimum recommended consumption is 1.5 kg / m²*
- *Allows the release of the repaired area to contact with water in 1 hour.*
- *In the case of settlement of the ceramic BAUTECH SEC RÁPIDO, it is recommended the use of a polymeric tile mortar.*
- *If there is need for mechanical protection, opt for a separating layer of Kraft paper or plastic canvas.*

PRECAUTIONS

- *Keeping the package closed when it is not in use.*
- *Never reuse the package for any purpose than the conditioning product.*
- *Store in original package in a dry, ventilated area away from heat sources.*
- *Keep out of reach of children and pets*
- *Prepare and apply the product always on environment vented to dryness*
- *It is recommended the use of personal protection equipment in accordance with Work and Worker Health rules, such as gloves, boots and goggles.*
- *In case of contact with skin and eyes, while the product is not cured, flush with current water for 15 minutes. If swallowed do not induce vomiting. In both cases, see a doctor immediately and take the package of the product.*

ESCROW

- *The information in this data sheet is based on laboratory testing and in our knowledge about the product. Measured values may vary due to environment. The BAUTECH warrants this product is free from manufacturing defects and the warranty extension is limited to the purchase price of your product, only if proven to be defective and when used as recommended. No other express or implied warranties, and no salesman, agent, distributor or dealer has the authority to extend, modify or suppress these provisions.*
- *For more information, please contact the Technical Department of BAUTECH*

LIMITATIONS

- *Do not apply when the surface temperature is or will be in the next 24 hours, temperature below 50 F ° or above 86 F ° (10 C ° or above 30 C °)*
- *Do not apply on bituminous surface such as asphalt or tar.*
- *It does not have chemical resistance.*